



**FIRE RATED GLASS**

**QUOTE REQUEST**

**ORDER FORM PO # \_\_\_\_\_**

**Customer Name:** \_\_\_\_\_

**Customer Contact:** \_\_\_\_\_

**Job Name:** \_\_\_\_\_

**Required Fire Rating**    20    45    60    90    180

**Application:**

\_\_\_\_\_ **Non-Temperature Rise Door (2736 Sq. In. Max. Size)**

\_\_\_\_\_ **Temperature Rise Door (100 Sq. In. Max. Size)**

\_\_\_\_\_ **Other than Door (See Labeling Guide for Max. Size)**

**NOTE:** SGC Fired-Rated Products are tested to UL9, UL10B, UL10C, NFPA 252, NFPA 257.

**These products are not heat barrier tested (ASTM E-119), not intended for fire walls where radiant heat transfer is a concern.**

**NON-SAFETY RATED**

**1/4 " Wired Glass**

- Diamond**
- Square**

**3/16" Schott Pyran Platinum**

**CPSC CAT II SAFETY RATED**

**3/16" Schott Pyran Platinum F (Surface Applied Film)**

**5/16" Schott Pyran Platinum L (Laminated)**

**Labeling:**

**Schott products are always labeled. Wired glass labeled on request.**   \_\_\_\_\_ **Labels required.**

\_\_\_\_\_ **Labels not required.**

**Attach Sizes and Quantities. Fax to: 315-437-8118**

**Check sizes against allowed maximums - see Labeling Guide doc.**