CRL CATEGORY II SAFETY BACKING TAPE

PRODUCT DESCRIPTION

A unique composite of copolymer film laminated to a bi-directional woven copolymer alloy to provide impact resistance in the shatter-proofing of mirrors. CRL Category II is designed to pass Category II shatter-proofing test, passing both vision and tape side tests. It provides trouble-free application with smooth laydown. No bubbling under extreme and adverse conditions. It has excellent adhesion to the mirror backing paints in international use, whether applied by spray, curtain or roller coating techniques. Special self-crosslinking, self-curing acrylic adhesive exhibits high initial tack, even under highly humid conditions. Adhesive strength increases with age to a truly permanent bond. Independent testing has shown the adhesive on CRL Category II to be non-contributory to copper and silver deterioration under normal ambients and when applied to paint-backed surfaces under salt spray conditions.

STANDARDS

Meets ANSI Z97.1-1984, HUD, CPSC, CAN 2-12.1, 16CFR1201 Category II British Standards BS-6206 Class A, 400 fp

APPLICATIONS

Suggested for use as a safety backing on silvered float glass and fully tempered glass mirrors, when 400 foot pound test requirements must be met. Recommended for mirrored wardrobe doors, bi-fold doors, shower and tub enclosures and furniture mirrors.



TECHNICAL DATA				
		<u>IMPERIA</u>	<u>.L</u>	METRIC
ADHESION:				
Peel (PSTC #1)	Immediate		nch width	
a	20 min. dwell	350 5 5	nch width	
Shear (PSTC #7)	Indefinite @	2 psi		15.0 KFa
MATERIAL:				
ADHESIVE:				
		moistu	e, high temperature, UV, chemicals,	
		oils,abr	asion, aging, mildew and fungus	
		·5	, & &	
HIGH TEMP. RESISTANCE:		212°F		100°C
				SEMPONERS CHARL
STANDARD SIZES:				
			48" (1219 m), 60" (1524 mm)	
Lengths: 600 ft. (183 m)				
			3" diameter (76.2 mm)	
		35 ATT 25		



The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties and are not intended to be used as specifications for defined applications. User must determine the product suitability for the end use application and assume all risks and liabilities. 2/3/00

PAGE 1 of 1

AVD3866_II_4/06

